

2M IP IR Mini Bullet


NBI4-62-R

Features

- Optimized Multiple Profile Streaming
- ROI(Region of Interest)
- Various Web Plug-in
- Smart AVC
- Advanced Built in ISP
- Fluid Integration Way
- Double Scan Sensor with Advanced Built in ISP (2M)



Dimension (mm)



Specification

Video

Image Sensor	1/2.8" 2.1M CMOS
Channels	1
Total Pixel	1945(H) X 1109(V)
Max Resolution	1920 X 1080
MIN. Illumination	2.8mm : 0.05Lux, 0Lux with IR (F2.0) 4.0mm : 0.09Lux, 0Lux with IR (F2.6)
Only installer Video Output	No
S/N(signal/noise) Ratio	50dB
Scanning Mode	Progressive Scan

Lens

Focal Length	2.8mm 4.0mm
Aperture	2.8mm :F2.0 / 4.0mm : F2.6
Lens Type	Fixed
IRIS Type	Auto Exposure
Horizontal Angle	2.8mm:111.0 / 4.0mm: 86.0

Operational

Shutter Speed	Auto / Manual (1/15 ~ 1/32000)
Auto Gain Control (AGC)	Yes
Day & Night	TDN (True Day & Night)
Digital Noise Reduction	3D DNR
Wide Dynamic Range (WDR)	WDR (2x)
Dynamic Range	120dB or above
IR LEDs	H2IR
IR Distance	70ft
Privacy Zone	Yes
Function	Motion Detection Mirror & Flip

Encoder (video & audio)

Video Compression	H.265 H.264 MJPEG
Support Resolution	H.265:1920x1080/1280x720/704x576/704x480/640x480/352x288/352x240 H.264:1920x1080/1280x720/704x576/704x480/640x480/352x288/352x240 MJPEG:1920x1080/1280x720/800x600/640x480/768x432/704x576/704x480/352x288/352x240
Multiple Profile Streaming Performance	1080p30 + D1(704x480 or 704x576) p30 with H.264, H.265 + MJPEG
Video BitRate	Yes
Bitrate Control	Multi Streaming CBR/VBR at H.265 (Controllable frame rate and Bandwidth)

Encoder (video & audio)

Video Bitrate extra comment	Multi-rate for Preview and Recording
Special Feature	Dynamic ROI(Region of Interest) Smart LBR

I/O & Event

Audio In / Out	No
Alarm In / Out	No
Mic	No
Event Trigger	Motion Alarm Network Disconnection Temperature Critical Illegal Login Schedule Sensor Detection
Event Notification	FTP E-Mail Alarm Out SD Card

Network

Ethernet	RJ45 (10/100Base-T)
Protocol	TCP/IP UDP AutoIP RTP(UDP/TCP) RTSP NTP HTTP HTTPS SSL DNS DDNS DHCP FTP SMTP ICMP SNMPv1/v2/v3(MIB-2) ONVIF
Security	HTTPS(SSL) IP filtering 802.1x Digest Authentication
SIP/VoIP Support	SIP VoIP
Application Programming I/F	CGI API ONVIF
Web viewer	Windows®
Video management software (VMS)	DW Spectrum® IPVMS
Support languages	English Korean Japanese
Edge storage	Micro SD Micro SDHC Micro SDXC
SD Card Socket	1

Electrical

Power Requirement	Adaptor is not included DC12V PoE IEEE 802.3af Class3
Power consumption	DC12V Max 4W PoE Max 5.5W

Environmental


Operating Temperature	-20°C ~ 50°C
Cold Start	No
Operating Humidity	10-90% RH(Non-Condensing)
IP Rating	IP67
Other Certification	FCC CE ROHS

Mechanical

Housing Model	BI4
---------------	-----

Mechanical	
Housing	Outdoor Bullet
Material	Aluminum-Die Casting
Color	White
Dimensions (W x D x H)	78.5mm 72.0mm 172.5mm
Weight	0.65kg

Compatible Accessories



BJC07

Junction Bracket