

5M IP Door Jamb Camera


NST11-65 (복사)

Features

- Optimized Multiple Profile Streaming
- ROI(Region of Interest)
- Various Web Plug-in
- Smart AVC
- Advanced Built in ISP
- Fluid Integration Way
- Double Scan Sensor with Advanced Built in ISP (5M)
- Pinhole camera can be easily adjusted to eye level, giving a clearer view of the face, even when a person is wearing a cap or hood.



Dimension (mm)



Specification

Video

Image Sensor	1/2.8" 5.14M CMOS
Channels	1
Total Pixel	2592(H) X 1944(V)
Max Resolution	2592 x 1944
MIN. Illumination	0.26Lux 0Lux with IR
Only installer Video Output	No
S/N(signal/noise) Ratio	50dB
Scanning Mode	Progressive Scan

Lens

Focal Length	3.7mm
Aperture	F2.5
Lens Type	Fixed
IRIS Type	Auto Exposure
Horizontal Angle	D : 115 , H : 87.6, V : 61.6

Operational

Shutter Speed	Auto / Manual (1/15 ~ 1/32000)
Auto Gain Control (AGC)	Yes
Day & Night	No
Digital Noise Reduction	3D DNR
Wide Dynamic Range (WDR)	WDR (2x)
Dynamic Range	120dB or above
IR LEDs	Non-IR
Privacy Zone	Yes
Function	Motion Detection Mirror & Flip

Encoder (video & audio)

Video Compression	H.265 H.264 MJPEG
Support Resolution	H.265 : 2592x1944/ 2560x1440/ 1920x1080/ 1280×720/ 800x600/ 704x576/ 768x432/ 704x480/ 640x480/ 640x360/ 352x288/ 352x240 H.264 : 2592x1944/ 2560x1440/ 1920x1080/ 1280×720/ 800x600/ 704x576/ 768x432/ 704x480/ 640x480/ 640x360/ 352x288/ 352x240 MJPEG : 1920x1080/1280x720/800x600/768x432/704x576/704x480/640x480/352x288/352x240
Multiple Profile Streaming Performance	2592x1944p30 + 480p30 with H.264,H265 + MJPEG
Video BitRate	Yes

Encoder (video & audio)

Bitrate Control	Multi Streaming CBR/VBR at H.265 (Controllable frame rate and Bandwidth)
Video Bitrate extra comment	Multi-rate for Preview and Recording
Audio Compression	No
Special Feature	Dynamic ROI(Region of Interest) Smart LBR

I/O & Event

Audio In / Out	No
Alarm In / Out	No
Mic	No
Event Trigger	Motion Alarm Network Disconnection Temperature Critical Illegal Login Schedule Sensor Detection
Event Notification	FTP E-Mail Alarm Out SD Card

Network

Ethernet	RJ45 (10/100Base-T)
Protocol	TCP/IP UDP AutoIP RTP(UDP/TCP) RTSP NTP HTTP HTTPS SSL DNS DDNS DHCP FTP SMTP ICMP SNMPv1/v2/v3(MIB-2) ONVIF
Security	HTTPS(SSL) IP filtering 802.1x Digest Authentication
SIP/VoIP Support	SIP VoIP
Application Programming I/F	CGI API ONVIF
Web viewer	Windows®
Video management software (VMS)	DW Spectrum® IPVMS
Support languages	English Korean Japanese
Edge storage	Micro SD Micro SDHC Micro SDXC
SD Card Socket	1

Electrical

Power Requirement	Adaptor is not included DC12V PoE IEEE 802.3af Class2
Power consumption	DC12V Max 4W PoE Max 4.8W

Environmental

Operating Temperature	-20°C ~ 50°C
Cold Start	No
Operating Humidity	10-90% RH(Non-Condensing)
Vandal Proof Casing	No
IP Rating	No
Other Certification	FCC CE ROHS

Mechanical	
Housing Model	ST10
Housing	Indoor Specialty
Material	Plastic
Color	White
Dimensions (W x D x H)	50.3mm 190mm
Weight	0.4kg